


ROBUST
VERSATILE
CLEAN HOLES

Diamond Core Bit



Features

- Wavy segments.
- High quality diamonds.
- Ejection slot.
- M16 shank.

Benefits

- Dry use.
- No vibration.
- Use on drilling machine (recommended speed 2500 rpm).

	Ø	N.S.	Lu	Ref.	Gencod	Qt.	Pack
	Lt 88						
	68	5	66	431D68	3336600145832	1	A
	82	6	66	431D82	3336600145849	1	A
	Lt 181						
	29	3	154	432D29	3336600145856	1	N
	35	3	154	432D35	3336600145863	1	M
	42	4	154	432D42	3336600145870	1	M
	52	4	154	432D52	3336600145887	1	M
	65	5	154	432D65	3336600145894	1	M



Plastic clip
European hole
Color label



Twistpack
European hole
Color label



Twistpack
Round eyelet
Color label



Implementation



1/ Pre-drill with Ø8 on the desired depth.

2/ Fit the bit on the adapter and insert the centering guide.



3/ Place the centering guide with the bit in the pre-hole in order to begin coring.



4/ Drill to the desired depth.

Ref.

431
432



see our
video on
YouTube

Accessories

	Lt	Ref.	Gencod	Qt.	Pack
	Compatible SDS-plus core bit adapter				
	100	367L0100	3336600063891	1	A
	170	367L0170	3336600063907	1	A
	220	367L0220	3336600063914	1	A
	320	367L0320	3336600063921	1	A
	Compatible SDS-plus & SPIT core bit adapter				
	100	368L100	3336600063938	1	A
	HEXA core bit adapter				
	100	433L0100	3336600145900	1	M
	220	433L0220	3336600146112	1	M
	320	433L0320	3336600146129	1	M

	Ø	Lt	Ref.	Gencod	Qt.
	Centering Guide				
	8	120	420D08L0120	3336600173699	1
	8	210	420D08L0210	3336600173705	1

	Ø	Lt	Larg.	Ref.	Gencod	Qt.
	Sharpening stone for diamond core bit					
	20	200	100	427	3336600155084	1



431C

SETS
PAGE
58

367
368
433



420

Drilling Ø 8 / Guide Ø 7

427

