

Bit Holder Fox II



Features

- Attachment DIN 3126 E 6,3. and compatible SDS+.
- For bits hexa 1/4" according to DIN 3126 C 6,3 and E 6,3.
- Permanent magnet.
- Cold forging process.

Benefits

- Quick ejection.
- Very high torsion resistance.
- Quick and easy manipulation with just one hand.
- Magnetic for handling the screws.



Designation	Qt.	Lt	Ref.	Gencod	Qt.	HT€
Bit holder Fox II	1	60	U648	3336600173156	1	19,90
Bit holder Fox II SDS-Plus	1	80	U638	3336600181212	1	21,78

Ref.

U648
U638



DIN 3126 E6,3

Bit Holder Standard

Features

- Attachment DIN 3126 E 6,3. and compatible SDS+.
- For hexa bits 1/4" according to DIN 3126 C 6,3 and E 6,3.
- Permanent magnet.
- Bit holding ring (sauf U628).
- Cold forging process.

Benefits

- Magnetic for handling the screws.
- Ideal for hard-to-reach areas, particularly with longer lengths (up to 250mm).



1 & 10
PIECES

Designation	Qt.	Lt	Ref.	Gencod	Qt.	Pack
NEW Bit holder Standard Quick-Lock	1	51	U626	3336600189119	1	R
Bit holder Standard	1	58	U628	3336600146792	1	R
NEW Bit holder Standard	10	58	U62810	3336600189164	1	R
Bit holder Standard	1	74	U629L074	3336600181243	1	R
Bit holder Standard	1	100	U629L100	3336600181250	1	D
Bit holder Standard	1	150	U629L150	3336600181267	1	D
Bit holder Standard	1	200	U629L200	3336600181274	1	D
Bit holder Standard	1	250	U629L250	3336600181281	1	D
Bit holder SDS-Plus	1	78	U635	3336600178229	1	R

U626
U628
U629
U635



DIN 3126 E6,3

Bit Holder Shorty



Features

- Attachment DIN 3126 E 6,3.
- Standard socket holder male square 1/4.

Benefits

- Its reduced length fits entirely in the chuck and makes it possible to use the power screwdriver/drill in tight spaces.
- Magnetic for handling the screws.



Designation	Qt.	Lt	Ref.	Gencod	Qt.
Bit holder Shorty	1	35	U633	3336600181236	1

U633



1/4" E6,3